

ICON SERIES

ICON RIGID

RECOMMENDED APPLICATIONS



CASINOS




BANKS



HIGH TRAFFIC AREAS



TIERED SEATING AND STAGES



SYSTEM NAME

Icon Rigid Heavy Grade 4.5kN

DESCRIPTION

Icon Rigid is widely used for finished floor heights over 800mm or areas that require a more rigid installation due to high load or traffic.

COMPLIANT STANDARDS

Australian Standard AS4154/AS4155

Australian Standard AS1170

NATA Testing Certification

ISO9239-1-2003

EN12825-2001

DIN4102-1-1998

SIZE 600mm x 600mm

DEPTH 33mm

CORE

Cementitious Compound

FINISH

ASP's standard powder coated finish.

CONSTRUCTION

The panels consist of a hardened steel top and bottom sheet plate with corrosion resistant protection, inside and out, encapsulating a structural cementitious core.

TOLERANCE

±0.25mm and a flatness tolerance of ±0.5mm measured on a diagonal across the top of the panel

CONNECTION

The panel is screw fixed on top of the stringer assembly to the pedestal head at all four corners

PERFORMANCE TO STANDARDS GUIDE PER AS4154 – 1993 AUSTRALIAN STANDARD – GENERAL ACCESS FLOORS

Load Level	Panel (kg)	System (kg/m² at 450mm FFH)
4.5kN Heavy Grade	14.2	45.9
STATIC PERFORMANCE (kN)		
Concentrated	Impact	Ultimate
4.5	0.4	13.5
DYNAMIC PERFORMANCE (kN) - Passes		
10 passes (wheel size 75x25mm)	10,000 passes (wheel size 150x50mm)	40,000 passes (wheel size 200x75mm)
4.4	3.3	2.25

Safety Factor: Panels must provide a minimum safety factor of three (3) times the concentrated load specified above in accordance with Australian Standards AS4154-1993



PEDESTAL SIZE

100mm x 100mm base plate

PEDESTAL CONSTRUCTION

Hot dipped galvanised steel pedestal base, head and rod. Finished with an ABS locating gasket.

PEDESTAL LOCKING

The pedestals will be provided with an adjusting and locking nut to maintain the assembly at a selected height, which requires a deliberate action to change the height setting, and which prevents vibration displacement.

PEDESTAL FINISH

Hot dipped galvanized finish.

PEDESTAL CONNECTION

The panel is screw fixed to the pedestal head at all four corners.

PEDESTAL FINISHED FLOOR HEIGHT (FFH)

The finished floor height of the access floor is measured from the sub floor to the top surface of the installed access floor.

STRINGER SIZE

31mm x 21mm x 1.2mm x 600mm

STRINGER CONSTRUCTION

Rectangular steel welded tube with 1.6mm sponge rubber foam.

STRINGER FINISH

Hot dipped galvanized finish.

STRINGER CONNECTION

The stringer is screw fixed to the pedestal head.